

RL-HB5328-SERIES

LED High Bay Light



0/1 -10V/DAL



180Lm/W



WARRANTY



IP65



MICROWAVE
SENSOR



IK10



50,000H



-30°C~+60°C



30°/60°/90°



360° cooling



RAPID HEAT
DISSIPATION





EASY
INSTALL




Size


400W




100W




150W



200W



240W



Parameters

Model NO.	RL-HB5328-SERIES				
Wattage	100W	150W	200W	240W	400W
Input voltage	AC 100V-265V				
Frequency	50HZ-60HZ				
Total harmonic distortion	≤9%				
DIM.OP	0-10V/1-10V/ DALI				
Power factor	>0.95				
LED luminous efficiency	130 LM/W				180 LM/W
LED BRAND	13000LM	19500LM	26000LM	31200LM	72000LM
Lumen	OSRAM/LIMILEDS				
Driver	SOSEN/PHILIPS/MEANWELL				
Color temperature	2800-6500K				
Beam angle	90°/120°			30°/ 60°/90°	
Lamp's efficiency	> 90%				
Illuminance uniformity	> 0.6				
Color rendering index	Ra>70				
Light distribution	Circular Symmetrical luminescence				
Light design	LED+ Lens Secondary Optical				
LED Junction temperature	≤66.5℃				
Working temperature	-30℃--+65℃				
Storage temperature	-30℃--+65℃				
IP Grade	IP65				
Working life-span	> 50.000H				
Warranty	5 Years				

Photometric diagrams

