

RL-HB5329-SERIES

LED High Bay Light



0/1-10V/DALI



140-170Lm/W



WARRANTY



IP65



WET RADET



MICROWAVE
SENSOR



IK10



50,000H



-30°C~+50°C



EASY
INSTALL



60°/90°/120°






360° Cooling



RAPID HEAT
DISSIPATION



Size






Sensor Optional



Sensor Optional



Photometric diagrams



Parameters

Model No.	RL-HB5329-SERIES			
Wattage Tunable	100W	150W	200W	240W
Efficiency	140-170Lm/W	140-170Lm/W	140-170Lm/W	140-170Lm/W
Luminous Flux	14000-17000Lm	21000-22500Lm	28000-34000Lm	33600-40800Lm
LED Type	Lumileds/Samsung			
DIM.OP	0-10V/1-10V/ DALI			
CCT	3000K/4000K/5000K/5700K/6500K			
CRI	> 70Ra(80Ra optional)			
Beam Angle	60°/90°/120°			
Power Supply	Sosen/ Lifud/Philips			
Input Voltage	AC220-240V/AC 100-277V			
Power Frequency	50/60Hz			
Power Factor	0.95			
Total Harmonic Distortion	< 15%			
SPD	6 KV			
Heat Radiator	ADC12 Aluminum alloy			
Lens Materia	CPC			
IK Rating	IK 10			
IP Rating	IP65			
Working Temperature	-30°C---+65°C			
Storing Temperature	-30°C---+65°C			
Lifetime(L70 Standard)	50,000 hours			
Warranty	5 Years			